

# S5-GC(25-40)K

Solis Three Phase Inverters



360 degree

## Model:

**400V:** S5-GC25K S5-GC30K S5-GC33K S5-GC36K S5-GC40K



### Efficient

- ▶ Max. efficiency 98.7%
- ▶ String current up to **16A**
- ▶ 3/4 MPPT design, supports multiple orientation system design
- ▶ Night time PID recovery function, increases overall system yield (optional)
- ▶ Wide voltage range and low startup voltage



### Safe

- ▶ IP66
- ▶ AFCI protection, proactively reduces fire risk
- ▶ Globally recognised branded componentry for longer life
- ▶ Intelligent redundant fan-cooling



### Smart

- ▶ Supports export power control
- ▶ Intelligent string monitoring, smart I-V curve scan
- ▶ Supports RS485, WiFi, GPRS
- ▶ Scan to register on SolisCloud, supports remote upgrade and control



### Economic

- ▶ Supports GPRS/WiFi communication with less wiring and reduced installation costs
- ▶ > 150% DC/AC ratio
- ▶ Supports high power modules for lower installation costs
- ▶ Supports aluminium wire access to reduce cost

## Datasheet

Model Name	S5-GC25K	S5-GC30K	S5-GC33K	S5-GC36K	S5-GC40K		
<b>Input DC</b>							
Recommended max. PV power	37.5 kW	45 kW	49.5 kW	54 kW	60 kW		
Max. input voltage			1100 V				
Rated voltage			600 V				
Start-up voltage			180 V				
MPPT voltage range			200-1000 V				
Max. input current	32 A / 32 A / 32 A			4*32 A			
Max. short circuit current	50 A / 50 A / 50 A			4*50 A			
MPPT number/Max. input strings number	3/6			4/8			
<b>Output AC</b>							
Rated output power	25 kW	30 kW	33 kW	36 kW	40 kW		
Max. apparent output power	27.5 kVA	33 kVA	36.3 kVA	39.6 kVA	44 kVA		
Max. output power	27.5 kW	33 kW	36.3 kW	39.6 kW	44 kW		
Rated grid voltage	3/N/PE, 220 V / 380 V, 230 V / 400 V						
Rated grid frequency	50 Hz / 60 Hz						
Rated grid output current	38.0 A / 36.1 A	45.6 A / 43.3 A	50.1 A / 47.6 A	54.7 A / 52.0 A	60.8 A / 57.7 A		
Max. output current	41.8 A	50.2 A	55.1 A	60.2 A	66.9 A		
Power Factor	>0.99 (0.8 leading - 0.8 lagging)						
THDi	<3%						
<b>Efficiency</b>							
Max. efficiency	98.5%		98.6%	98.7%			
EU efficiency	98.1%		98.2%	98.3%			
<b>Protection</b>							
DC reverse-polarity protection	Yes						
Short circuit protection	Yes						
Output over current protection	Yes						
Surge protection	DC Type II / AC Type II						
Grid monitoring	Yes						
Anti-islanding protection	Yes						
Temperature protection	Yes						
Strings monitoring	Yes						
I/V Curve scanning	Yes						
Integrated PID recovery	Optional						
Integrated AFCI (DC arc-fault circuit protection)	Yes <sup>(1)</sup>						
Integrated DC switch	Optional						
<b>General Data</b>							
Dimensions (W*H*D)	647*629*252 mm						
Weight	37 kg						
Topology	Transformerless						
Self consumption (night)	<1 W						
Operating ambient temperature range	-25 ~ +60°C						
Relative humidity	0-100%						
Ingress protection	IP66						
Cooling concept	Intelligent redundant fan-cooling						
Max. operation altitude	4000 m						
Grid connection standard	G98 or G99, VDE-AR-N 4105 / VDE V 0124, EN 50549-1, VDE 0126 / UTE C 15 / VFR:2019, RD 1699 / RD 244 / UNE 206006 / UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC60068, IEC 61683, EN 50530						
Safety/EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4						
<b>Features</b>							
DC connection	MC4 connector						
AC connection	OT terminal						
Display	LCD						
Communication	RS485, Optional: Wi-Fi, GPRS						

(1) Activation required.