

---

# SolarEdge Home Backup Interface

## Single Phase, for Europe

BI-EU1P

BACKUP



### Flexible Backup Interface

- / Automatically provides backup power to home loads in the event of grid interruption
- / Flexibility in which loads to back up - the entire home or selected loads
- / Scalable solution to support higher power & higher capacity
- / Seamless integration with the SolarEdge Home Hub Inverter to manage and monitor both PV generation and energy storage

# / SolarEdge Home Backup Interface

## Single Phase, for Europe

### BI-EU1P

	BI-EU1P <sup>(1)</sup>	UNITS
<b>GRID CONNECTION</b>		
AC Current Input	100	A
AC Voltage Line – Neutral (Min/Nom/Max)	184 / 230 / 264	V
AC Frequency Range	50 / 60	Hz
On Grid to Off Grid Switchover Time	< 3	sec
<b>OUTPUT TO DISTRIBUTION PANEL</b>		
Maximum AC Current Output	100	A
AC Voltage Line – Neutral (Min/Nom/Max)	184 / 230 / 264	V
AC Frequency Range	50 / 60	Hz
Overvoltage Category	III	
<b>ADDITIONAL FEATURES</b>		
Supported Grid Topologies	TT, TN-S, TN-C-S <sup>(2)</sup>	
Operation During Backup	Disconnection of phase + N from external grid; PE to Neutral connection on load side / disconnection configuration option on internal grid	
Communication	RS485 and SolarEdge Home Network <sup>(3)</sup>	
Energy Meter (for Import/Export)	Integrated <sup>(3)</sup> , 1.25% accuracy	
Manual Control Over Microgrid Interconnection Device	Yes	
<b>STANDARD COMPLIANCE</b>		
Safety	IEC/EN 62109-1	
Emissions	IEC 61000-6-2, IEC 61000-6-3, IEC 61000-3-11, IEC 61000-3-12, EN55011	
<b>INSTALLATION SPECIFICATIONS</b>		
Supported Inverters	SolarEdge Home Hub Inverter – Single Phase	
AC from Grid / Loads Conductor Cross Section	6 – 25	mm <sup>2</sup>
Grid / Loads Conduit Diameter	14 – 22	mm
Communication Cable Cross Section	0.2 – 1.5	mm <sup>2</sup>
Communication Gland Diameter	5 – 15	mm
Weight	< 5	kg
Noise	< 50	dB(A)
Operating Temperature Range	-40 to +50	°C
Relative Humidity Range	0 – 100	%
Protection Rating	IP65 – outdoor and indoor	
Dimensions (H x W x D)	390 x 238 x 147	mm
Pollution Degree	3	
Maximum Altitude Rating	2000	m

(1) Applicable for PN BI-NEUNU-1P-01.

(2) For other topologies please consult with SolarEdge support.

(3) Pending firmware support.