







Temperature Sensors

Victron products can make use of temperature sense information to improve accuracy of battery charging. There is a range of various sensors that you can use depending on your product. Some come included, others can be purchased separately. See the datasheet if the required product (eg Multi, Quattro, BMV) to know if the sensor comes included.

| Temperature Sensor | VE.Bus Smart Dongle (1) | Smart Battery Sense (3M) | Smart Battery Sense (10M) | Temp. Sensor for Quattro, MultiPlus & GX Device | Temp. Sensor for BMV | Temp. sensor type C |
|-------------------------|---|---|---|---|---|---|
| Picture |  |  |  |  |  |  |
| Products Supported | VE.Bus devices | Bluetooth enabled VE.Direct MPPTs and Smart IP43 Charger | Bluetooth enabled VE.Direct MPPTs and Smart IP43 Charger | MultiPlus, Quattro, Compatible GX devices (Cerbo GX, Venus GX, etc), VE.Can MPPT, Lynx Shunt VE.Can, Skylla-S, Sylla-TG, Skylla-i and Charger | Battery Monitors with Temp Support - eg BMV-702 & 712, SmartShunt & VE.Bus Smart Dongle | Inverter RS Smart Solar, MPPT RS |
| Victron Part Number | ASS030537010 | SBS050100200 | SBS050150200 | ASS000001000 | ASS000100000 | ASS000020000 |
| Temperature on VRM | Yes | No | No | MultiPlus - Yes, Venus GX - Yes, VE.Can MPPT - Yes, Lynx Shunt VE.Can - Yes | Yes | No |
| Product Page | Link | Link | Link | Link | Link | Link |
| Manual | Accessory Manual | Accessory Manual | Accessory Manual | See Inverter / Charger / Device Product Manual | See Battery Monitor Product Manual | See MPPT RS, or Inverter RS Smart Solar Manual |
| VE.Smart Networking | Yes | Yes | Yes | No | Yes with BMV-712; Yes with dongle for BMV-702 | No |
| Modifying cable length? | n/a | yes (2) | yes (2) | yes (2) | yes (3) | yes (2) |

Notes:

1. You can mount the dongle itself directly on the battery. It has an internal temperature measurement. There are also terminals you can connect an external probe to as well, you must use the probe part - ASS000100000.
2. Cable length may be altered without any issue - within reason. The same wiring is used as a

power supply for the Smart Battery Sense as well, too much resistance in the cabling will cause a too low voltage reading. If desired, cable length may be shortened without any issue.

3. Although discouraged and unsupported, cable length may also be extended if necessary for the installation - providing the additional length is kept short and conductor cross section is sufficient, a slight increase in cable resistance will not negatively effect the temperature reading accuracy. Note that a notable increase in cable resistance to the BMV temperature sensor will also effect the voltage reading accuracy.

From:

<https://www.victronenergy.com/live/> - **Victron Energy**

Permanent link:

https://www.victronenergy.com/live/temperature_sensors

Last update: **2024-05-08 08:16**

