# **M90 PRO**

#### LITHIUM IRON PHOSPHATE BATTERY







(A) Grade A+ Cells

Manufactured using the premium quality, fresh LiFePO4 raw materials for top-tier performance.

8000 High Cycle Efficiency

Up to 8000 Cycles @ DOD 80%, ensuring a cost-effective ownership experience.

Advanced Touch Screen

Multi-language colorful touch screen for clear monitoring of battery parameters, with easy control over settings.

**Extended Durability** 

Enjoy a longer lifespan with our low-maintenance, stable chemistry batteries.

Integrated Safety Measures

Enhanced with a built-in Battery Management System (BMS) to prevent misuse.

Heat Resilience Engineered for optimal

Engineered for optimal performance, even in extreme temperatures up to +60°C.

Superior Safety

Designed with advanced safety features to guarantee secure usage and storage.

Smart BMS Compatible with multiple inverter brands.













The MOTOMA M PRO Series LFP battery is an advanced energy solution designed to deliver a service life of 15 years or more, providing exceptional performance for a wide range of applications. With a lifespan of up to 8000 cycles, it ensures reliable and efficient energy storage for many years.

Equipped with a multi-language and colored touch LCD screen, the M PRO Series allows users to monitor the battery status, access detailed reports, and fully control settings. Its intelligent BMS ensures safety, along with SOC design and a communication protocol compatible with various inverter brands.

### **Applications**

- Power Generation System (Solar and Wind Power System,etc.)
- Household Energy Storage System
- Auto Control System &ATM Machine
- Electronic Apparatus and Equipment
- Emergency Light & Emergency Backup
- Power Supply & Alarm / Security System
- Communication Power & DC PowerElectric Power System (EPS)
- Uninterruptable Power System (UPS)

#### Certificates













### **Technical Parameter**

M90 PRO
51.2V
320Ah
16.384kWh
43.2V~58.4V
200A
200A
0°C~45°C
-20°C~60°C
IP20
8000 time
RS485 / CAN / RS232
990*505*200 mm
126.6 kg

### **Charge Performance**

Recommended Charge Current	30A
Maximum Charge Current	200A
Peak Charge Current	210A (1s)
Recommended Charge Voltage	57.6V
BMS Charge Cut-Off Voltage	58.4V (3.65V/Cell)
Reconnect Voltage	54.08V (3.38V/Cell)
Balancing Voltage	54.4V (3.4V/Cell)
Balancing Current	40mA

# **Discharge Performance**

Recommended Discharge Current	30A
Maximum Continuous Discharge Current	200A
Peak Discharge Current	210A (10s)
BMS Discharge Cut-Off Current	250A (500ms)
Recommended Low Voltage Disconnect	48V (3.0V/Cell)
BMS Discharge Cut-Off Voltage	43.2V (2.7V/Cell)
Reconnect Voltage	49.6V (3.1V/Cell)
Short Circuit Protection	250~500us

# **Packaging**

Packaging Type	1 Battery / UN Wooden Box
Package Dimension ( LxWxH )	1248x609x372 mm
Package Weight ( GW )	156.6 KG



